

Printing date 15.02.2024 Version number 5 Revision: 15.02.2024

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier

Trade name: Haftgrundierung Putzgrund (DIY)

Safety data sheet no.: 49PB20990

1.2 Relevant identified uses of the substance or mixture and uses advised against

No further relevant information available.

Application of the substance / the mixture

Construction chemicals

Coating

1.3 Details of the supplier of the safety data sheet

Manufacturer/Supplier:

Saint Gobain Weber GmbH

Schanzenstr. 84 D-40549 Düsseldorf +49(0)211/91369-0

e-mail: Produktsicherheit@sg-weber.de

1.4 Emergency telephone number:

Emergency medical information in case of poisoning:

Poison Information Centre Mainz - Tel.: +49 (0) 6131 19240 (advice in German or English)

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture

Classification according to Regulation (EC) No 1272/2008

The product is not classified according to the CLP regulation.

2.2 Label elements

Labelling according to Regulation (EC) No 1272/2008 Void

Hazard pictograms Void

Signal word Void

Hazard statements Void

Additional information:

Information according to Biocidal Products Regulation (EU) 528/2012: contains

Active substance for preservation during storage: reaction mass of 5-chloro-2-methyl-2H-isothiazol-3-one [EC no. 247-500-7] and 2-methyl-2H-isothiazol-3- one [EC no. 220-239-6] (3:1) (CAS no.: 55965-84-9)

EUH208 Contains reaction mass of 5-chloro-2- methyl-2H-isothiazol-3-one [EC no. 247-500-7] and 2-methyl-2H-isothiazol-3- one [EC no. 220-239-6] (3:1), 1,2-benzisothiazol-3(2H)-one. May produce an allergic reaction.

EUH210 Safety data sheet available on request.

EUH211 Warning! Hazardous respirable droplets may be formed when sprayed. Do not breathe spray or mist.

2.3 Other hazards

Results of PBT and vPvB assessment

PBT: Does not contain PBT substances.

vPvB: Does not contain vPvB substances.

Determination of endocrine-disrupting properties Not applicable.

EUG



Printing date 15.02.2024 Version number 5 Revision: 15.02.2024

Trade name: Haftgrundierung Putzgrund (DIY)

(Contd. of page 1)

SECTION 3: Composition/information on ingredients

3.2 Mixtures

Description: Acrylate dispersion

CAS: 14808-60-7	Silicon dioxide (Quartz sand)	10-20%
EINECS: 238-878-4	substance with a Community workplace exposure limit	
CAS: 13463-67-7 EINECS: 236-675-5 Index number: 022-006-00-2 Reg.nr.: 01-2119489379-17-xxxx	titanium dioxide Carc. 2, H351	1-2%
CAS: 2634-33-5 EINECS: 220-120-9 Index number: 613-088-00-6 Reg.nr.: 01-2120761540-60-xxxx	1,2-benzisothiazol-3(2H)-one Eye Dam. 1, H318; Aquatic Acute 1, H400 (M=1); Acute Tox. 4, H302; Skin Irrit. 2, H315; Skin Sens. 1, H317 Specific concentration limit: Skin Sens. 1;H317: C ≥ 0.05 %	<0.05%
CAS: 55965-84-9 EC number: 611-341-5 Index number: 613-167-00-5	reaction mass of 5-chloro-2- methyl-2H-isothiazol-3-one [EC no. 247-500-7] and 2-methyl-2H-isothiazol-3- one [EC no. 220-239-6] (3:1) Acute Tox. 3, H301; Acute Tox. 2, H310; Acute Tox. 2, H330; Skin Corr. 1C, H314; Eye Dam. 1, H318; Aquatic Acute 1, H400 (M=100); Aquatic Chronic 1, H410 (M=100); Skin Sens. 1A, H317, EUH071 Specific concentration limits: Skin Corr. 1C;H314: C ≥ 0.6 % Skin Irrit. 2; H315: 0.06 % ≤ C < 0.6 % Eye Dam. 1; H318: C ≥ 0.6 % Eye Irrit. 2; H319: 0.06 % ≤ C < 0.6 % Skin Sens. 1A; H317: C ≥ 0.0015 %	≥0.00025-<0.0015

SVHC Void

Additional information For the wording of the listed hazard phrases refer to section 16.

SECTION 4: First aid measures

4.1 Description of first aid measures

General information Immediately remove any clothing soiled by the product.

After inhalation Supply fresh air; consult doctor in case of complaints.

After skin contact

Immediately wash with water and soap and rinse thoroughly.

If skin irritation continues, consult a doctor.

After eye contact

Rinse opened eye for several minutes under running water. Then consult doctor. Rinse liquid should be tempered (20-30°C).

After swallowing Drink plenty of water and provide fresh air. Call for a doctor immediately.

(Contd. on page 3)



Printing date 15.02.2024 Version number 5 Revision: 15.02.2024

Trade name: Haftgrundierung Putzgrund (DIY)

(Contd. of page 2)

Information for doctor None

4.2 Most important symptoms and effects, both acute and delayed

No further relevant information available.

4.3 Indication of any immediate medical attention and special treatment needed

No further relevant information available.

SECTION 5: Firefighting measures

5.1 Extinguishing media

Suitable extinguishing agents Use fire extinguishing methods suitable to surrounding conditions.

5.2 Special hazards arising from the substance or mixture No further relevant information available.

5.3 Advice for firefighters

Protective equipment: Use methods suitable to surrounding conditions.

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

Wear protective clothing.

6.2 Environmental precautions: Do not allow product to reach sewage system or any water course.

6.3 Methods and material for containment and cleaning up:

Pick up mechanically.

Dispose of the material collected according to regulations.

6.4 Reference to other sections See Section 13 for disposal information.

SECTION 7: Handling and storage

7.1 Precautions for safe handling

Keep receptacles tightly sealed.

Store in cool, dry place in tightly closed receptacles.

Information about fire - and explosion protection: No special measures required.

7.2 Conditions for safe storage, including any incompatibilities

Storage

Requirements to be met by storerooms and receptacles:

Store in a cool location.

Store only in unopened original receptacles.

Information about storage in one common storage facility: Store away from foodstuffs.

Further information about storage conditions:

Store in cool, dry conditions in well sealed receptacles.

Protect from heat and direct sunlight.

Protect from freezing.

Recommended storage temperature: 5-30°C.

7.3 Specific end use(s) No further relevant information available.

EUG



Printing date 15.02.2024 Version number 5 Revision: 15.02.2024

Trade name: Haftgrundierung Putzgrund (DIY)

(Contd. of page 3)

SECTION 8: Exposure controls/personal protection

8.1 Control parameters

Ingredients with limit values that require monitoring at the workplace:

The product does not contain any relevant quantities of materials with critical values that have to be monitored at the workplace.

DNELs			
	3-67-7 titanium		
		Level 1.25 mg/m³ (worker local long term value)	
		0.21 mg/m³ (consumer local long term value)	
CAS: 2634	1-33-5 1,2-benzi	othiazol-3(2H)-one	
Dermal	Derived No Effe	Level 0.966 mg/kgxday (worker systemic long term value)	
		0.345 mg/kgxday (consumer systemic long term value)	
Inhalative	Derived No Effe	Level 6.81 mg/m³ (worker systemic long term value)	
		1.2 mg/m³ (consumer systemic long term value)	
CAS: 5590		mass of 5-chloro-2- methyl-2H-isothiazol-3-one [EC no. 247-500 hyl-2H-isothiazol-3- one [EC no. 220-239-6] (3:1)	
Oral	Derived No Effe	Level 0.09 mg/kgxday (consumer systemic long term value)	
Inhalative	Derived No Effe	Level 0.02 mg/m³ (worker local long term value)	
		0.02 mg/m³ (consumer local long term value)	
PNECs			
CAS: 2634	1-33-5 1,2-benzi	othiazol-3(2H)-one	
	•	ration 3 mg/kgxdwt (earth rating factor)	
		ration 0.000403 mg/l (sea water rating factor)	
		0.00403 mg/l (fresh water rating factor)	
CAS: 5590		mass of 5-chloro-2- methyl-2H-isothiazol-3-one [EC no. 247-500 hyl-2H-isothiazol-3- one [EC no. 220-239-6] (3:1)	
Predicted	No-Effect Conce	ration 0.01 mg/kgxdwt (earth rating factor)	
Predicted	No-Effect Conce	ration 0.00339 mg/l (sea water rating factor)	
		0.00339 mg/l (fresh water rating factor)	
CAS N	o. / Designation	of material / % / Type / Value / Unit	
CAS: 1480	08-60-7 Silicon o	oxide (Quartz sand)	
BOELV (E		ong-term value: 0.1* mg/m³ respirable fraction	
MAK (Ger	(Germany) Long-term value: 0.05 mg/m³ alveolengängige Fraktion		
GV (Denm	total:,**total, respirabel, EK		
LEP (Spai	n)	Long-term value: 0.05 mg/m³ *Fracción resp:n,d,y	
TWA (Italy) Long-term A2, (j)		ong-term value: 0.025 mg/m³ 2, (j)	
TWA (Italy			



Printing date 15.02.2024 Version number 5 Revision: 15.02.2024

Trade name: Haftgrundierung Putzgrund (DIY)

	(Contd. of page 4)					
VLE (Portugal)	Long-term value: 0.025 mg/m³					
	Resp.;A2; fibrose pulmonar; cancro do pulmão					
OEL (Sweden)	Long-term value: 0.1 mg/m³					
	C, M, respirabel fraktion					
HTP (Finland)	Long-term value: 0.05 0.1* mg/m³					
	alveolijae;*sitovat raja-arvot, pöly					
CAS: 2634-33-5	CAS: 2634-33-5 1,2-benzisothiazol-3(2H)-one					
MAK (Germany)	vgl.Abschn.IIb und Xc					
CAS: 55965-84-	9 reaction mass of 5-chloro-2- methyl-2H-isothiazol-3-one [EC no. 247-500-7]					
	and 2-methyl-2H-isothiazol-3- one [EC no. 220-239-6] (3:1)					
MAK (Germany)						
	vgl.Abschn.Xc					

Additional information:

The applicable TRGS 900 (MAK list) was used as the basis for the preparation and/or revision of this safety data sheet.

8.2 Exposure controls

Appropriate engineering controls No further data; see section 7.

Individual protection measures, such as personal protective equipment

General protective and hygienic measures:

The usual precautionary measures are to be adhered to when handling chemicals.

Avoid contact with the eyes and skin.

Do not eat or drink while working.

Keep away from foodstuffs, beverages and feed.

Wash hands before breaks and at the end of work.

Immediately remove all soiled and contaminated clothing.

Respiratory protection: Not necessary if room is well-ventilated.

Hand protection

Protective gloves.

The glove material has to be impermeable and resistant to the product/ the substance/ the mixture. Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

Material of gloves

Butyl rubber, BR

Nitrile rubber, NBR

Recommended thickness of the material: ≥ (Butyl) 0.7 mm; (NBR) 0.4 mm

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a mixture of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

Penetration time of glove material

Breakthrough time: > 480 min

Value for the permeation: Level ≤ 6

The exact breaktrough time has to be found out by the manufacturer of the protective gloves and has to be observed.

Eye/face protection Safety glasses.

Body protection: Protective work clothing.

- EUG



Printing date 15.02.2024 Version number 5 Revision: 15.02.2024

Trade name: Haftgrundierung Putzgrund (DIY)

(Contd. of page 5)

SECTION 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties

General Information

Colour: According to product specification

Odour: Characteristic
Odour threshold: Not determined.
Melting point/freezing point: 0 °C (DIN ISO 3016)

Boiling point or initial boiling point and boiling

range 100 °C (DIN)

Lower and upper explosion limit

Lower: Not determined.
Upper: Not determined.
Flash point: Not applicable
Auto-ignition temperature: Not determined.
Decomposition temperature: Not determined.
pH at 20 °C 9.0 (DIN 19261)

Viscosity:

Kinematic viscosity dynamic:Not determined.
Not determined.

Solubility

Water: Fully miscible
Partition coefficient n-octanol/water (log value) Not determined.
Vapour pressure: Not determined.

Density and/or relative density

Density at 20 °C: 1.45 g/cm³ (DIN 51757)

Bulk density:

Vapour density

Not applicable.

Not determined.

9.2 Other information None.

Appearance:

Form: Pasty

Important information on protection of health

and environment, and on safety.

Ignition temperature: Product is not self-igniting.

Explosive properties: Product does not present an explosion hazard.

Minimum ignition energy

Solvent separation test: Not applicable.

Solvent content:

 Organic solvents:
 0.0 %

 EU-VOC (%)
 0.10 %

 EU-VOC (g/L)
 1.4 g/l

Change in condition Softening point/range

Oxidising properties Not determined. Evaporation rate Not determined.

Information with regard to physical hazard

classes

Explosives Void Flammable gases Void

(Contd. on page 7)



Printing date 15.02.2024 Version number 5 Revision: 15.02.2024

Trade name: Haftgrundierung Putzgrund (DIY)

		(Contd. of page (
Aerosols	Void	
Oxidising gases	Void	
Gases under pressure	Void	
Flammable liquids	Void	
Flammable solids	Void	
Self-reactive substances and mixtures	Void	
Pyrophoric liquids	Void	
Pyrophoric solids	Void	
Self-heating substances and mixtures	Void	
Substances and mixtures, which emit		
flammable gases in contact with water	Void	
Oxidising liquids	Void	
Oxidising solids	Void	
Organic peroxides	Void	
Corrosive to metals	Void	
Desensitised explosives	Void	

SECTION 10: Stability and reactivity

10.1 Reactivity No further relevant information available.

10.2 Chemical stability

Thermal decomposition / Conditions to be avoided:

No decomposition if used according to specifications.

- 10.3 Possibility of hazardous reactions No dangerous reactions known
- 10.4 Conditions to avoid No further relevant information available.
- **10.5 Incompatible materials:** No further relevant information available.
- 10.6 Hazardous decomposition products: No dangerous decomposition products known.

SECTION 11: Toxicological information

11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008

Acute toxicity Based on available data, the classification criteria are not met.

LD/LC50 values relevant for classification:

Compone	ents	1	Type	1	Value	1	Species
CAS: 131	CAS: 1317-65-3 calcium carbonate						
Oral	LD50	>5,000 r	ng/kg (F	Rat)			
aqueous	aqueous dispersion of a copolymer based on styrene and acrylic acid ester						
Oral	LD50	>2,000-10,000 mg/kg (Rat)					
CAS: 134	CAS: 13463-67-7 titanium dioxide						
Oral	LD50	>5,000 mg/kg (Rat)					
CAS: 263	CAS: 2634-33-5 1,2-benzisothiazol-3(2H)-one						
Oral	LD50	>490 mg	g/kg (Ra	t)			
Dermal	LD50	>2,000 r	ng/kg (F	Rat)			

(Contd. on page 8)



Printing date 15.02.2024 Version number 5 Revision: 15.02.2024

Trade name: Haftgrundierung Putzgrund (DIY)

(Contd. of page 7)

CAS: 55965-84-9 reaction mass of 5-chloro-2- methyl-2H-isothiazol-3-one [EC no. 247-500-7 and 2-methyl-2H-isothiazol-3- one [EC no. 220-239-6] (3:1)				
Oral	LD50	457 mg/kg (Rat)		
Dermal	LD50	660 mg/kg (Rabbit)		

Skin corrosion/irritation Based on available data, the classification criteria are not met.

Serious eye damage/irritation Based on available data, the classification criteria are not met.

Respiratory or skin sensitisation

Inhalative LC50/4 h 2.36 mg/l (Rat)

May cause an allergic skin reaction to already sensitised individuals (supplemental labelling EUH208 in Europe)

Germ cell mutagenicity Based on available data, the classification criteria are not met.

Carcinogenicity Based on available data, the classification criteria are not met.

Reproductive toxicity Based on available data, the classification criteria are not met.

STOT-single exposure Based on available data, the classification criteria are not met.

STOT-repeated exposure Based on available data, the classification criteria are not met.

Aspiration hazard Based on available data, the classification criteria are not met.

11.2 Information on other hazards

Endocrine disrupting properties

None of the ingredients is listed.

SECTION 12: Ecological information

12.1 Toxicity

Aquatic toxicity: No further relevant information available.

Type of test	Type of test / Effective concentration / Method / Assessment					
CAS: 1317-6	CAS: 1317-65-3 calcium carbonate					
LC50/96h	>10,000 mg/l (Oncorhynchus mykiss (Rainbow trout))					
EC50/48h	h >1,000 mg/l (Daphnia magna)					
EC50/72h	0/72h >200 mg/l (Algae)					
CAS: 13463-	67-7 titanium dioxide					
IC50/72h	1 mg/l (Fish)					
LC50/48h	>100 mg/l (aquatic invertebrates)					
LC50/96h	>100 mg/l (Fish)					
EC50/48h	>100 mg/l (aquatic invertebrates)					
EC50/72h	>100 mg/l (Algae)					
NOEC (72h)	≥10 mg/l (aquatic algae and cyanobacteria)					
NOEC (96h)	≥1 mg/l (aquatic plants other than algae)					
NOEC (21d)	≥100 mg/l (aquatic invertebrates)					
NOEC (28d)	≥100 mg/l (aquatic invertebrates)					
	≥0.07 mg/l (Fish)					
CAS: 2634-3	3-5 1,2-benzisothiazol-3(2H)-one					
LC50/96h	2.2 mg/l (Fish)					
EC50/16h	0.4 mg/l (Pseudomonas putida (Bacteria))					
EC50/48h	2.9 mg/l (aquatic invertebrates)					
	(Contd. on page 9)					



Printing date 15.02.2024 Version number 5 Revision: 15.02.2024

Trade name: Haftgrundierung Putzgrund (DIY)

	(Contd. of page 8)
EC50/72h	0.11 mg/l (aquatic algae and cyanobacteria)
	0.067 mg/l (Pseudomonas putida (Bacteria))
NOEC (72h)	0.0403 mg/l (aquatic algae and cyanobacteria)
CAS: 55965-	84-9 reaction mass of 5-chloro-2- methyl-2H-isothiazol-3-one [EC no. 247-500-7] and 2-methyl-2H-isothiazol-3- one [EC no. 220-239-6] (3:1)
LC50/48h	0.18 mg/l (Daphnia magna)
LC50/96h	0.282 mg/l (Daphnia magna)
	0.19-0.3 mg/l (Fish)
EC50/24h	0.109 mg/l (Daphnia magna)
	0.0107 mg/l (aquatic algae and cyanobacteria)
EC50/48h	0.16 mg/l (Daphnia magna)
	0.0181-0.0371 mg/l (aquatic algae and cyanobacteria)
EC50/96h	0.0357 mg/l (aquatic algae and cyanobacteria)
EC50/72h	0.0063-0.0273 mg/l (aquatic algae and cyanobacteria)
NOEC (14d)	0.035 mg/l (Daphnia magna)
NOEC (21d)	0.011-1.05 mg/l (Daphnia magna)
NOEC (28d)	0.098 mg/l (Fish)

12.2 Persistence and degradability No further relevant information available.

Other information: The product is not easily biodegradable.

12.3 Bioaccumulative potential

CAS: 2634-33-5 1,2-benzisothiazol-3(2H)-one

EBAB 0.7 log Pow

CAS: 55965-84-9 reaction mass of 5-chloro-2- methyl-2H-isothiazol-3-one [EC no. 247-500-7] and 2-methyl-2H-isothiazol-3- one [EC no. 220-239-6] (3:1)

EBAB 0.75 log Pow

12.4 Mobility in soil No further relevant information available.

12.5 Results of PBT and vPvB assessment

PBT: Does not contain PBT substances.

vPvB: Does not contain vPvB substances.

12.6 Endocrine disrupting properties

The product does not contain substances with endocrine disrupting properties.

12.7 Other adverse effects No further relevant information available.

Remark: The product contains substances which causes severe clouding in water

Behaviour in sewage processing plants:

Type of test / Effective concentration / Method / Assessment
CAS: 13463-67-7 titanium dioxide
EC 50 (3h) 1,000 mg/l (microorganisms)
CAS: 2634-33-5 1,2-benzisothiazol-3(2H)-one
EC 50 (3h) 10.3 mg/l (microorganisms)
CAS: 55965-84-9 reaction mass of 5-chloro-2- methyl-2H-isothiazol-3-one [EC no. 247-500-7] and 2-methyl-2H-isothiazol-3- one [EC no. 220-239-6] (3:1)
EC 50 (3h) 4.5 mg/l (microorganisms)



Printing date 15.02.2024 Version number 5 Revision: 15.02.2024

Trade name: Haftgrundierung Putzgrund (DIY)

Additional ecological information:

(Contd. of page 9)

General notes: Do not allow product to reach ground water, water course or sewage system.

SECTION 13: Disposal considerations

13.1 Waste treatment methods

Recommendation

After prior treatment product has to be landfilled adhering to the regulations pertaining to the disposal of particularly hazardous waste.

European waste catalogue

08 01 20 aqueous suspensions containing paint or varnish other than those mentioned in 08 01 19

Uncleaned packaging:

Recommendation:

Empty contaminated packagings thoroughly. They may be recycled after thorough and proper cleaning. **Recommended cleaning agent:** Water, if necessary together with cleansing agents.

SECTION 14: Transport informa	tion
14.1 UN number or ID number ADR, ADN, IMDG, IATA	Void
14.2 UN proper shipping name ADR, ADN, IMDG, IATA	Void
14.3 Transport hazard class(es)	
ADR, ADN, IMDG, IATA Class	Void
14.4 Packing group ADR, IMDG, IATA	Void
14.5 Environmental hazards:	Not applicable.
14.6 Special precautions for user	Not applicable.
14.7 Maritime transport in bulk accordi IMO instruments	ing to Not applicable.
Transport/Additional information:	Not dangerous according to the above specifications.
UN "Model Regulation":	Void

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

Regulation (EC) No 1907/2006 (REACH) (Candidate List, Annexes XIV and XVII)

Regulation (EC) No 1272/2008 (CLP)

Regulation (EU) 2020/878 (amending REACH Annex II on the compilation of safety data sheets)

(Contd. on page 11)



Printing date 15.02.2024 Version number 5 Revision: 15.02.2024

Trade name: Haftgrundierung Putzgrund (DIY)

(Contd. of page 10)

Directive 2004/42/EC (VOC), cf. section 9

Regulation (EU) 528/2012 (Biocidal Product Regulation), cf. section 2

Labelling according to Regulation (EC) No 1272/2008 cf. section 2

Directive 2012/18/EU

Named dangerous substances - ANNEX I None of the ingredients is listed.

DIRECTIVE 2011/65/EU on the restriction of the use of certain hazardous substances in electrical and electronic equipment – Annex II

None of the ingredients is listed.

REGULATION (EU) 2019/1148

Annex I - RESTRICTED EXPLOSIVES PRECURSORS (Upper limit value for the purpose of licensing under Article 5(3))

None of the ingredients is listed.

Annex II - REPORTABLE EXPLOSIVES PRECURSORS

None of the ingredients is listed.

Regulation (EC) No 273/2004 on drug precursors

None of the ingredients is listed.

Regulation (EC) No 111/2005 laying down rules for the monitoring of trade between the Community and third countries in drug precursors

None of the ingredients is listed.

15.2 Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

SECTION 16: Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

This Safety Data Sheets is in compliance with Regulation (EC) No 1907/2006, Article 31 as amended by Regulation (EU) 2020/878.

Relevant phrases

The following list of relevant hazard statements is the full text of hazard statements mentioned elsewhere in this safety data sheet (in particular in the section 3) and is reported as required by the Regulation (EC) No 1907/2006 (REACH), Annex II, and the following amendments (Regulation (EU) 2020/878). The statements mentioned here do not refer to the product itself, but refer to the individual ingredients in the products, and are provided for information.

- H301 Toxic if swallowed.
- H302 Harmful if swallowed.
- H310 Fatal in contact with skin.
- H314 Causes severe skin burns and eye damage.
- H315 Causes skin irritation.
- H317 May cause an allergic skin reaction.
- H318 Causes serious eye damage.
- H319 Causes serious eye irritation.
- H330 Fatal if inhaled.
- H351 Suspected of causing cancer.
- H400 Very toxic to aquatic life.
- H410 Very toxic to aquatic life with long lasting effects.

EUH071 Corrosive to the respiratory tract.

Department issuing SDS: Product safety department.

(Contd. on page 12)



Printing date 15.02.2024 Version number 5 Revision: 15.02.2024

Trade name: Haftgrundierung Putzgrund (DIY)

(Contd. of page 11)

Contact: Produktsicherheit@sg-weber.de; tel. +49(0)2363/399-210

Abbreviations and acronyms:

RID: Règlement international concernant le transport des marchandises dangereuses par chemin de fer (Regulations Concerning the International Transport of Dangerous Goods by Rail)

ADR: Accord relatif au transport international des marchandises dangereuses par route (European Agreement Concerning the International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

IATA: International Air Transport Association

IATA-DGR: Dangerous Goods Regulations by the "International Air Transport Association" (IATA)

ICAO: International Civil Aviation Organisation

GHS: Globally Harmonised System of Classification and Labelling of Chemicals EINECS: European Inventory of Existing Commercial Chemical Substances ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

DNEL: Derived No-Effect Level (REACH)

PNEC: Predicted No-Effect Concentration (REACH)

LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent

PBT: Persistent, Bioaccumulative and Toxic

SVHC: Substances of Very High Concern (REACH regulation)

vPvB: very Persistent and very Bioaccumulative

Acute Tox. 3: Acute toxicity - Category 3

Acute Tox. 4: Acute toxicity - Category 4

Acute Tox. 2: Acute toxicity - Category 2

Skin Corr. 1C: Skin corrosion/irritation - Category 1C

Skin Irrit. 2: Skin corrosion/irritation – Category 2

Eye Dam. 1: Serious eye damage/eye irritation - Category 1

Skin Sens. 1: Skin sensitisation – Category 1

Skin Sens. 1A: Skin sensitisation – Category 1A

Carc. 2: Carcinogenicity – Category 2

Aquatic Acute 1: Hazardous to the aquatic environment - acute aquatic hazard - Category 1

Aquatic Chronic 1: Hazardous to the aquatic environment - long-term aquatic hazard - Category 1

* Data compared to the previous version altered.

According to Annex II of the REACH regulation, the modified sections in this version of the Safety Data Sheet in comparison with the previous one are marked with asterisks.

EUG