

SECTION 1: Identification of the substance/mixture and of the company/undertaking**1.1 Product identifier**Trade name **weber Flexkleber Feinsteinzeug**

Safety data sheet no.: 49PD21254

1.2 Relevant identified uses of the substance or mixture and uses advised against

No further relevant information available.

Application of the substance / the mixture Construction chemicals**1.3 Details of the supplier of the safety data sheet****Manufacturer/Supplier:**

Saint Gobain Weber GmbH

Schanzenstr. 84

D-40549 Düsseldorf

+49(0)211/91369-0

e-mail: Produktsicherheit@sg-weber.de

1.4 Emergency telephone number:

Emergency medical information in case of poisoning:

Poison Information Centre Mainz - Tel.: +49 (0) 6131 19240 (advice in German or English)

SECTION 2: Hazards identification**2.1 Classification of the substance or mixture****Classification according to Regulation (EC) No 1272/2008**

The product is not classified, according to the CLP regulation.

2.2 Label elements**Labelling according to Regulation (EC) No 1272/2008** Void**Hazard pictograms** Void**Signal word** Void**Hazard statements** Void**2.3 Other hazards****Results of PBT and vPvB assessment****PBT:** Does not contain PBT substances.**vPvB:** Does not contain vPvB substances.**SECTION 3: Composition/information on ingredients****3.2 Mixtures****Description:** Mixture of substances listed below with non hazardous additions.**Dangerous components:**

CAS: 14808-60-7 EINECS: 238-878-4	Silicon dioxide (Quartz sand) substance with a Community workplace exposure limit	25-50%
CAS: 1317-65-3 EINECS: 215-279-6	calcium carbonate substance with a Community workplace exposure limit	2-5%

(Contd. on page 2)

Safety Data Sheet

according to 1907/2006/EC, Article 31

Printing date 03.04.2023

Version number 1

Revision: 03.04.2023

Trade name weber Flexkleber Feinsteinzeug

(Contd. of page 1)

CAS: 7778-18-9 EINECS: 231-900-3 Reg.nr.: 01-2119444918-26-xxxx	calcium sulphate, different hydrate levels CaSO ₄ x n H ₂ O (n = 0; 1/2; 2) substance with a Community workplace exposure limit	1-2%
CAS: 65997-15-1 EINECS: 266-043-4	cement portland, grey ⚠ Eye Dam. 1, H318; ⚠ Skin Irrit. 2, H315; Skin Sens. 1, H317; STOT SE 3, H335, EUH203 Specific concentration limits: Skin Irrit. 2; H315: C ≥ 1 % Eye Dam. 1; H318: C ≥ 1 %	≥0.1-<1%

SVHC Void

Additional information

The mixture is "low chromate" according to the Regulation (EC) No 1272/2008 within the product shelf-life, so that the classification with H317 is not applicable, when the packing was not opened in the meantime.

For the wording of the listed hazard phrases refer to section 16.

SECTION 4: First aid measures

4.1 Description of first aid measures

General information Immediately remove any clothing soiled by the product.

After inhalation Supply fresh air; consult doctor in case of complaints.

After skin contact

Immediately wash with water and soap and rinse thoroughly.

Generally the product does not irritate the skin.

After eye contact

Rinse opened eye for several minutes under running water. Rinse liquid should be tempered (20-30°C).

After swallowing

Rinse out mouth with water. Do not induce vomiting. Seek medical attention and present this data sheet.

4.2 Most important symptoms and effects, both acute and delayed

No further relevant information available.

4.3 Indication of any immediate medical attention and special treatment needed

No further relevant information available.

SECTION 5: Firefighting measures

5.1 Extinguishing media

Suitable extinguishing agents

Use fire extinguishing methods suitable to surrounding conditions.

5.2 Special hazards arising from the substance or mixture No further relevant information available.

5.3 Advice for firefighters

Protective equipment: Use methods suitable to surrounding conditions.

EUG

(Contd. on page 3)

Safety Data Sheet

according to 1907/2006/EC, Article 31

Printing date 03.04.2023

Version number 1

Revision: 03.04.2023

Trade name weber Flexkleber Feinsteinzeug

(Contd. of page 2)

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

Wear protective equipment. Keep unprotected persons away.

6.2 Environmental precautions: Do not allow product to reach sewage system or any water course.

6.3 Methods and material for containment and cleaning up: Pick up mechanically.

6.4 Reference to other sections See Section 13 for disposal information.

SECTION 7: Handling and storage

7.1 Precautions for safe handling

Provide suction extractors if dust is formed.

Prevent formation of dust.

Information about fire - and explosion protection: No special measures required.

7.2 Conditions for safe storage, including any incompatibilities
Storage
Requirements to be met by storerooms and receptacles:

Store only in unopened original receptacles.

Information about storage in one common storage facility:

Do not store together with acids.

Store away from foodstuffs.

Further information about storage conditions:

Store in cool, dry conditions in well sealed receptacles.

Protect from humidity and water.

7.3 Specific end use(s) No further relevant information available.

SECTION 8: Exposure controls/personal protection

8.1 Control parameters
Ingredients with limit values that require monitoring at the workplace:
DNELs
CAS: 7778-18-9 calcium sulphate, different hydrate levels CaSO₄ x n H₂O (n = 0; 1/2; 2)

Oral	Derived No Effect Level	1.52 mg/kgxday (consumer systemic long term value) 11.4 mg/kgxday (consumer systemic short term value)
Inhalative	Derived No Effect Level	21.17 mg/m ³ (worker systemic long term value) 5,082 mg/m ³ (worker systemic short term value) 5.29 mg/m ³ (consumer systemic long term value) 3,811 mg/m ³ (consumer systemic short term value)

PNECs
CAS: 65996-69-2 Slags, ferrous metal, blast furnace

Predicted No-Effect Concentration	1,000 mg/kgxdwt (earth rating factor)
Predicted No-Effect Concentration	500 mg/l (sea water rating factor)
Predicted No-Effect Concentration	5,000 mg/l (fresh water rating factor)

(Contd. on page 4)

Safety Data Sheet

according to 1907/2006/EC, Article 31

Printing date 03.04.2023

Version number 1

Revision: 03.04.2023

Trade name weber Flexkleber Feinsteinzeug

(Contd. of page 3)

CAS No. / Designation of material / % / Type / Value / Unit	
CAS: 14808-60-7 Silicon dioxide (Quartz sand)	
BOELV (European Union)	Long-term value: 0.1* mg/m ³ *respirable fraction
MAK (Germany)	Long-term value: 0.05 mg/m ³ alveolengängige Fraktion
GV (Denmark)	Short-term value: 0.6* 0.2** mg/m ³ Long-term value: 0.3* 0.1** mg/m ³ *total; **total, respirabel, EK
LEP (Spain)	Long-term value: 0.05 mg/m ³ *Fracción resp:n,d,y
TWA (Italy)	Long-term value: 0.025 mg/m ³ A2, (j)
VLE (Portugal)	Long-term value: 0.05 mg/m ³ Resp.;A2; fibrose pulmonar; cancro do pulmão
OEL (Sweden)	Long-term value: 0.1 mg/m ³ C, M, respirabel fraktion
HTP (Finland)	Long-term value: 0.05 0.1* mg/m ³ alveolijae;*sitovat raja-arvot, pöly
CAS: 1317-65-3 calcium carbonate	
TWA (Italy)	Long-term value: 10 mg/m ³ (e)
CAS: 7778-18-9 calcium sulphate, different hydrate levels CaSO₄ x n H₂O (n = 0; 1/2; 2)	
AGW (Germany)	Long-term value: 6 A mg/m ³ DFG
LEP (Spain)	Long-term value: 10 mg/m ³ e
TWA (Italy)	Long-term value: 10 mg/m ³ (i)
VLE (Portugal)	Long-term value: 10 mg/m ³ Fração inalável; Sintomas nasais
CAS: 65997-15-1 cement portland, grey	
AGW (Germany)	Long-term value: 5 E mg/m ³ DFG
LEP (Spain)	Long-term value: 4 mg/m ³ fracción respirable: e, d
TWA (Italy)	Long-term value: 1 mg/m ³ (e, j), A4
VLE (Portugal)	Long-term value: 1 mg/m ³ Fração resp.;A4,função pulm.,sintomas resp.,asma
HTP (Finland)	Long-term value: 5* 1** mg/m ³ *hengittyvä pöly, **alveolijae

Additional Occupational Exposure Limit Values for possible hazards during processing:

Total inhalable dust: 10 mg/m³Respirable dust (< 5 µm): 4 mg/m³

(Contd. on page 5)

-EUG

Safety Data Sheet
according to 1907/2006/EC, Article 31

Printing date 03.04.2023

Version number 1

Revision: 03.04.2023

Trade name weber Flexkleber Feinsteinzeug

(Contd. of page 4)

Additional information:

The applicable TRGS 900 (MAK list) was used as the basis for the preparation and/or revision of this safety data sheet.

8.2 Exposure controls

Appropriate engineering controls No further data; see section 7.

Individual protection measures, such as personal protective equipment**General protective and hygienic measures:**

The usual precautionary measures are to be adhered to when handling chemicals.

Keep away from foodstuffs, beverages and feed.

Immediately remove all soiled and contaminated clothing.

Wash hands before breaks and at the end of work.

Avoid contact with the eyes and skin.

Respiratory protection:

Use suitable respiratory protective device in case of insufficient ventilation.

In case of brief exposure or low pollution use respiratory filter device.

In case of intensive or longer exposure use self-contained respiratory protective device.

Short term filter device:

Filter P2.

Hand protection

Protective gloves.

The glove material has to be impermeable and resistant to the product/ the substance/ the mixture.

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

Material of gloves

Nitrile impregnated cotton gloves complying with the standard EN 374-1.

Recommended thickness of the material: ≥ 0.11 mm

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a mixture of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

Penetration time of glove material

Breakthrough time: > 480 min

Value for the permeation: Level ≤ 6

The exact breakthrough time has to be found out by the manufacturer of the protective gloves and has to be observed.

Eye/face protection Tightly sealed goggles

Body protection: Protective work clothing.

SECTION 9: Physical and chemical properties**9.1 Information on basic physical and chemical properties****General Information**

Colour: According to product specification

Odour: Characteristic

Odour threshold: Not determined.

Melting point/freezing point: Undetermined.

Boiling point or initial boiling point and boiling range Undetermined.

Flammability Product is not flammable.

(Contd. on page 6)

Safety Data Sheet
according to 1907/2006/EC, Article 31

Printing date 03.04.2023

Version number 1

Revision: 03.04.2023

Trade name weber Flexkleber Feinsteinzeug

(Contd. of page 5)

Lower and upper explosion limit

Lower:	Not determined.
Upper:	Not determined.
Flash point:	Not applicable
Auto-ignition temperature:	Not determined.
Decomposition temperature:	Not determined.
pH at 20 °C	> 12.0 (DIN 19261) In water

Viscosity:

Kinematic viscosity Not applicable.

Kinematic viscosity

dynamic: Not applicable.

Solubility

Water: Insoluble

Partition coefficient n-octanol/water (log value) Not determined.

Vapour pressure: Not applicable.

Vapour pressure:

Density and/or relative density

Density: Not determined

Bulk density: Not determined.

Vapour density Not applicable.

Particle characteristics See section 3.

9.2 Other information

None.

Appearance:

Form: Powder

Important information on protection of health and environment, and on safety.

Ignition temperature: Product is not self-igniting.

Explosive properties: Product does not present an explosion hazard.

Minimum ignition energy

Solvent content:

Organic solvents: 0.0 %

EU-VOC (g/L)

Solids content: 100.0 %

Change in condition

Softening point/range

Oxidising properties Not determined.

Evaporation rate Not applicable.

Information with regard to physical hazard

classes

Explosives Void

Flammable gases Void

Aerosols Void

Oxidising gases Void

Gases under pressure Void

Flammable liquids Void

Flammable solids Void

Self-reactive substances and mixtures Void

Pyrophoric liquids Void

(Contd. on page 7)

Safety Data Sheet
according to 1907/2006/EC, Article 31

Printing date 03.04.2023

Version number 1

Revision: 03.04.2023

Trade name weber Flexkleber Feinsteinzeug

(Contd. of page 6)

Pyrophoric solids	Void
Self-heating substances and mixtures	Void
Substances and mixtures, which emit flammable gases in contact with water	Void
Oxidising liquids	Void
Oxidising solids	Void
Organic peroxides	Void
Corrosive to metals	Void
Desensitised explosives	Void

SECTION 10: Stability and reactivity

10.1 Reactivity No further relevant information available.

10.2 Chemical stability

Thermal decomposition / Conditions to be avoided:

No decomposition if used according to specifications.

10.3 Possibility of hazardous reactions

Reacts with light alloys in the presence of moisture to form hydrogen

10.4 Conditions to avoid No further relevant information available.

10.5 Incompatible materials: No further relevant information available.

10.6 Hazardous decomposition products: No dangerous decomposition products known.

SECTION 11: Toxicological information

11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008

Acute toxicity Based on available data, the classification criteria are not met.

LD/LC50 values relevant for classification:

Components	Type	Value	Species
CAS: 65996-69-2 Slags, ferrous metal, blast furnace			
Oral	LD50	>2,000 mg/kg	(Rat)
Dermal	LD50	>4,000 mg/kg	(Rat)
CAS: 1317-65-3 calcium carbonate			
Oral	LD50	>5,000 mg/kg	(Rat)
CAS: 7778-18-9 calcium sulphate, different hydrate levels CaSO₄ x n H₂O (n = 0; 1/2; 2)			
Oral	LD50	>2,000 mg/kg	(Rat)
CAS: 65997-15-1 cement portland, grey			
Dermal	LD50	>2,000 mg/kg	(Rabbit)

Skin corrosion/irritation Based on available data, the classification criteria are not met.

Serious eye damage/irritation Based on available data, the classification criteria are not met.

Respiratory or skin sensitisation Based on available data, the classification criteria are not met.

Germ cell mutagenicity Based on available data, the classification criteria are not met.

Carcinogenicity Based on available data, the classification criteria are not met.

Reproductive toxicity Based on available data, the classification criteria are not met.

STOT-single exposure Based on available data, the classification criteria are not met.

STOT-repeated exposure Based on available data, the classification criteria are not met.

Aspiration hazard Based on available data, the classification criteria are not met.

(Contd. on page 8)

Safety Data Sheet
according to 1907/2006/EC, Article 31

Printing date 03.04.2023

Version number 1

Revision: 03.04.2023

Trade name weber Flexkleber Feinsteinzeug

(Contd. of page 7)

11.2 Information on other hazards

Endocrine disrupting properties

None of the ingredients is listed.

SECTION 12: Ecological information

12.1 Toxicity

Aquatic toxicity: No further relevant information available.

Type of test / Effective concentration / Method / Assessment

CAS: 65996-69-2 Slags, ferrous metal, blast furnace

LC50/96h	>100 mg/l (Leuciscus idus (Orfe))
LC0/96h	>100 mg/l (Leuciscus idus (Orfe))
EC50/72h	>90,000 mg/l (Algae)
NOEC (72h)	50-100 mg/l (Algae)
NOEC (21d)	1,563 mg/l (Daphnia magna)
EC 0/48h	>100 mg /l (Daphnia magna)

CAS: 1317-65-3 calcium carbonate

LC50/96h	>10,000 mg/l (Oncorhynchus mykiss (Rainbow trout))
EC50/48h	>1,000 mg/l (Daphnia magna)
EC50/72h	>200 mg/l (Algae)

CAS: 7778-18-9 calcium sulphate, different hydrate levels CaSO4 x n H2O (n = 0; 1/2; 2)

LC50/48h	79-1,970 mg/l (Daphnia magna)
LC50/96h	>79 mg/l (Oryzias latipes (Japanese medaka)) 79-2,980 mg/l (Fish)
EC50/72h	>79 mg/l (Selenastrum capricornutum (Green algae))

12.2 Persistence and degradability No further relevant information available.

Other information: The product is not easily biodegradable.

12.3 Bioaccumulative potential No further relevant information available.

12.4 Mobility in soil No further relevant information available.

12.5 Results of PBT and vPvB assessment

PBT: Does not contain PBT substances.

vPvB: Does not contain vPvB substances.

12.6 Endocrine disrupting properties

The product does not contain substances with endocrine disrupting properties.

12.7 Other adverse effects No further relevant information available.

Remark:

The product contains substances which cause a local pH change and thus have a detrimental effect on fish and bacteria.

The product contains substances which causes severe clouding in water

Behaviour in sewage processing plants:

Type of test / Effective concentration / Method / Assessment

CAS: 65996-69-2 Slags, ferrous metal, blast furnace

EC 50 (3h)	>10,000 mg/l (Activated sludge)
------------	---------------------------------

(Contd. on page 9)

Trade name weber Flexkleber Feinsteinzeug

(Contd. of page 9)

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

Regulation (EC) No 1907/2006 (REACH) (Candidate List, Annexes XIV and XVII)

Regulation (EC) No 1272/2008 (CLP)

Regulation (EU) 2020/878 (amending REACH Annex II on the compilation of safety data sheets)

Directive 2012/18/EU

Named dangerous substances - ANNEX I None of the ingredients is listed.

DIRECTIVE 2011/65/EU on the restriction of the use of certain hazardous substances in electrical and electronic equipment – Annex II

None of the ingredients is listed.

REGULATION (EU) 2019/1148

Annex I - RESTRICTED EXPLOSIVES PRECURSORS (Upper limit value for the purpose of licensing under Article 5(3))

None of the ingredients is listed.

Annex II - REPORTABLE EXPLOSIVES PRECURSORS

None of the ingredients is listed.

Regulation (EC) No 273/2004 on drug precursors

None of the ingredients is listed.

Regulation (EC) No 111/2005 laying down rules for the monitoring of trade between the Community and third countries in drug precursors

None of the ingredients is listed.

15.2 Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

SECTION 16: Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

Relevant phrases

H315 Causes skin irritation.

H317 May cause an allergic skin reaction.

H318 Causes serious eye damage.

H335 May cause respiratory irritation.

EUH203 Contains chromium (VI). May produce an allergic reaction.

Department issuing SDS: Product safety department.

Contact: Produktsicherheit@sg-weber.de; tel. +49(0)2363/399-210

Abbreviations and acronyms:

RID: Règlement international concernant le transport des marchandises dangereuses par chemin de fer (Regulations Concerning the International Transport of Dangerous Goods by Rail)

ADR: Accord relatif au transport international des marchandises dangereuses par route (European Agreement Concerning the International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

IATA: International Air Transport Association

IATA-DGR: Dangerous Goods Regulations by the "International Air Transport Association" (IATA)

ICAO: International Civil Aviation Organisation

GHS: Globally Harmonised System of Classification and Labelling of Chemicals

(Contd. on page 11)

Safety Data Sheet
according to 1907/2006/EC, Article 31

Printing date 03.04.2023

Version number 1

Revision: 03.04.2023

Trade name weber Flexkleber Feinsteinzeug

(Contd. of page 10)

EINECS: European Inventory of Existing Commercial Chemical Substances
ELINCS: European List of Notified Chemical Substances
CAS: Chemical Abstracts Service (division of the American Chemical Society)
DNEL: Derived No-Effect Level (REACH)
PNEC: Predicted No-Effect Concentration (REACH)
LC50: Lethal concentration, 50 percent
LD50: Lethal dose, 50 percent
PBT: Persistent, Bioaccumulative and Toxic
SVHC: Substances of Very High Concern (REACH regulation)
vPvB: very Persistent and very Bioaccumulative
Skin Irrit. 2: Skin corrosion/irritation – Category 2
Eye Dam. 1: Serious eye damage/eye irritation – Category 1
Skin Sens. 1: Skin sensitisation – Category 1
STOT SE 3: Specific target organ toxicity (single exposure) – Category 3

EUG